

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number  
**WO 2005/018130 A2**

(51) International Patent Classification<sup>7</sup>: **H04L**  
(21) International Application Number:  
PCT/IL 2004/000739

MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(22) International Filing Date: 11 August 2004 (11.08.2004)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
60/494,575 13 August 2003 (13.08.2003) US

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and  
(72) Inventor: RAPHAELI, Dan [IL/IL]; Halamed Hei 19,  
44394 Kfar Saba (IL).


Declaration under Rule 4.17:  
— of inventorship (Rule 4.17(iv)) for US only

Published:  
— without international search report and to be republished  
upon receipt of that report

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: ANALOG SIGNALS SAMPLER PROVIDING DIGITAL REPRESENTATION THEREOF



(57) Abstract: A method and a corresponding system for sampling at least one analog signal (54) and providing digital representa-  
tion thereof (59). Disclosed an analog circuit (51) featuring high bandwidth, high gain, and low current consumption, wherein that  
analog circuit is implemented by low accuracy components. The analog circuit is integrated with a control unit (52). The control unit  
is keeping error outputs of the system at a minimal value so that the total effect of the control unit is canceling the effect of the input  
signals. By knowing the effect of the control unit, the at least one analog input signals (54) can be approximated. The control unit  
is using discrete value signals (58). Digital representation of these discrete value signals (57) is feed to a DSP that is reconstructing  
the input signal by knowing the effect of the control unit and the model of the sampler.